Isolation of Safety Critical Functions on our Machines and Equipment are **Engineered in Accordance with the Relevant Standards**



HAZARD ANALYSIS + SAFETY FUNCTION + RISK ASSESSMENT = SAFETY INTEGRITY. THINK SAFE, WORK SAFE - BE SAFE

YOU CAN DEPEND ON OUR RISK BASED APPROACH TO ACHIEVE HIGHER LEVELS OF SAFETY.

ABN: 81 113 707 092

<u>D</u>ouble <u>H</u>ead <u>U</u>ncoiler <u>Light</u> <u>Weight</u>

DHU-LW



Series	DHU-LW series	
Coil Width (mm)	300	400
Coil Weight (kg)	1000	
Coil I.D. (mm)	Ø508	
Coil O.D. (mm)	Ø1200	
Mandrel expansion	Manual Operation	
Mandrel Expansion Range (mm)	480 ~ 520	
Mandrel Brake	Manually	
Uncoiler Rotate	Manual Operation	
Uncoiler Position Lock	By Foot Paddle	
Coil Keeper (pcs)	8	

OPTIONS

- » 2 x Uncoil motors
- Variable Speed Inverter
- Sensor beam loop control
- 2 sets x Air operated snubber arms (required if material is more than 2.5 mm thick)

Standard Accessories:

- Narrow coil keepers (8 pieces)
- Heavy duty link bar type expansion
- Manually operated mandrel brake
- Manually operated head rotation
- Foot pedal unlocks head for rotation

All specifications, dimensions and design characteristics shown are subject to change without notice.