**Isolation of Safety Critical Functions** on our Machines and Equipment are **Engineered in Accordance with the Relevant Standards** 



HAZARD ANALYSIS + SAFETY FUNCTION + RISK ASSESSMENT = SAFETY INTEGRITY.

THINK SAFE. WORK SAFE - BE SAFE

YOU CAN DEPEND ON OUR RISK BASED APPROACH TO ACHIEVE HIGHER LEVELS OF SAFETY.

ABN: 81 113 707 092

## **D**ouble **H**ead **U**ncoiler **M**edium **W**eight DHU-MW



Series	DHU-MW series					
Coil Width (mm)	300	400	500	600	700	800
Coil Weight (kg)	3000					
Coil I.D. (mm)	Ø508					
Coil O.D. (mm)	Ø1200					
Mandrel expansion	Manual Operation					
Mandrel Expansion Range (mm)	480 ~ 520					
Mandrel Brake	Manually					
Uncoiler Rotate	Manual Operation					
Uncoiler Position Lock	By Foot Paddle					
Coil Keeper (pcs)	8					

## **OPTIONS:**

- 2 x Uncoil motors
- Variable Speed Inverter
- Sensor beam loop control
- Motorised head rotation
- Air operated mandrel disc brake (both sides)
- 2 sets Air operated snubber arms
- 2 sets Hydraulic operated snubber arms
- » Hydraulic mandrel expansion (both sides)

## **Standard Accessories:**

- Narrow coil keepers (8 pieces)
- Heavy duty link bar type expansion
- Manually operated mandrel brake
- Manually operated head rotation
- Foot pedal unlocks head for rotation

All specifications, dimensions and design characteristics shown are subject to change without notice.