Isolation of Safety Critical Functions on our Machines and Equipment are **Engineered in Accordance with the Relevant Standards**



ABN: 81 113 707 092

HAZARD ANALYSIS + SAFETY FUNCTION + RISK ASSESSMENT = SAFETY INTEGRITY.

THINK SAFE, WORK SAFE - BE SAFE

YOU CAN DEPEND ON OUR RISK BASED APPROACH TO ACHIEVE HIGHER LEVELS OF SAFETY.

<u>S</u>ingle <u>H</u>ead <u>U</u>ncoiler

<u>Light</u> <u>Weight</u>

SHU-LW



Series	SHU-LW series	
Coil width (mm)	300	400
Coil Weight (kg)	1000	
I.D. of coil (mm)	Ø508	
O.D. of coil (mm)	Ø1200	
Mandrel expansion	Manual Operation	
Expansion Range (mm)	480 ~ 520	
Coil Keeper (pcs)	4	

OPTIONS

- Uncoil motor .75Kw
- Variable Speed Inverter
- Sensor beam loop control
- Air operated snubber arms (required if material thickness is more than 2.5mm)

Standard Accessories:

- Narrow coil keepers (4 pieces)
- Heavy duty link bar type expansion
- Manually operated mandrel brake

All specifications, dimensions and design characteristics shown are subject to change without notice.